

IntexForms, Inc.

GlassFiber Reinforced Custom Products

Material Safety Data Sheet

I Product Identification

Trade Name: *GFRG** (Glassfiber Reinforced Gypsum)
*Stonetex** (Glassfiber Reinforced Faux Stone)

Manufacturer's Name: **IntexForms, Inc.**

Address (as labeled): **5421 84th Street., Sacramento, CA 95828**
Tel: 916-381-6343 Fax: 916-381-6344

Date Prepared or Revised: January 1, 2019 Prepared by: J McCoy

II Hazardous Ingredients

<u>Chemical Names</u>	<u>CAS Numbers</u>	<u>Percent</u>
Fiberglass	65997-17-3	6%
Gypsum (non-hazardous)	10101-41-4	94%

Exposure Limits in Air:

<u>Chemical Names</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>Other</u>
Fiberglass	10 mg/m ³	15 mg/m ³	(10mg/m ³ in CA)
Gypsum	none	none	

III Physical Properties

Vapor Density (air = 1): **N/A** Melting Point or Range (F): **N/A**
Specific Gravity: 2.5 approx. Boiling Point or Range (F): **N/A**
Solubility in Water: 0.2% Evaporation Rate (Butyl Acetate = 1): **N/A**
Vapor Pressure, mmHG or 20% C: N/A
Appearance and Odor Appearance: Material comes in solid "form molded" shapes.
Odor: **none**

How to detect this substance: Warning properties of substance as a gas/vapor/dust or mist: **N/A**

IV Fire and Explosion

Flash Point (F) (give method): Non-Combustible
Auto-Ignition Temperature (F): N/A
Flammable Limits in Air (Volume %): N/A Lower (LEL)___ Upper (UEL)___
Fire Extinguishing Materials: That which is appropriate for surrounding fire.
___ Water Spray ___ Carbon Dioxide ___ Other
___ Foam ___ Dry Chemical

IV Fire and Explosion: cont'd...

Special Firefighting Procedures: **none**
Unusual Fire and Explosion Hazards: **none**

V Health Hazard Information

Inhaled: Dust from grinding or cutting may cause temporary irritation.
Contact with Skin or Eyes: Dust may cause irritation, temporary itching of skin.
Absorbed Through Skin: N/A
Swallowed: No known hazard.

Health Effects or Risks from Exposure:

Acute: Exposure to glass fibers in the dust from this product may cause irritation of the skin and less frequently, irritation of the eyes, nose or throat. Cement dust is a respiratory irritant and may dry the skin.

Chronic: No chronic health effects from exposure of fibrous glass. Gypsum is regarded as a nuisance dust.

First Aid: Emergency Procedures
Eye Contact: Wash with distilled water and consult physician if irritation persists.
Skin Contact: Wash with water.
Inhaled: No emergency procedure required.
Swallowed: No emergency procedure required.

Suspected Cancer Agent: **No.** This products ingredients are not found in the lists.
 Yes. Federal OSHA___ NTP___ IARC___

California employers using Cal/OSHA: *Regulated carcinogens must register with Cal/OSHA and the Federal OSHA carcinogen lists are similar.*

Medical Conditions Aggravated by Exposure: Those prone to allergies, asthma, bronchitis or pulmonary disease may experience increased irritation to the nose, throat, eyes or skin.

VI Reactivity Data

Stability: x Stable ___ Unstable
Conditions to Avoid: None. This material will lose its integrity when submersed in water.
Incompatibility (materials to avoid): None.
Hazardous decomposition products (including combustion products): If heated to 1450°C, will release SO & CAE.
Hazardous Polymerization: ___ May Occur x Will not Occur
Conditions to Avoid: Keep product dry to maintain integrity.

VII Spill, Leak and Disposal Procedures

Spill Response Procedures: N/A

Preparing Wastes for Disposal (container type, neutralization etc.): Normal disposal as for any dry, inert dust (from cutting) or solids.

Note: Dispose of all wastes in accordance with Federal, State and Local regulations.

VIII Special Handling Information

Ventilation and Engineering Controls: Local exhaust, if above TLV, during cutting or grinding.

Respiratory Protection: NIOSH approved respirator for *dust* if above TLV during cutting or grinding.

Eye Protection: Dust goggles or safety glasses during cutting or grinding.

Gloves: Light weight or work gloves may help reduce skin irritation from dust.

Other Clothing and Equipment: Coveralls or work clothes to protect street clothes from dust.

Work Practices, Hygienic Practice: Keep dust production to a minimum. Keep work area clean. Do not use compressed air to “blow down” clothing. Wash exposed skin surfaces regularly with soap and water.

Other Handling and Storage Requirements: Store in dry area.

Protective Measures during Maintenance of Contaminated Equipment: N/A